

DOSERING ACTIVE TIRE BALANCE

För Off Road

Däck Dimension	Gram		Däck Dimension	Gram	
14"			16.5"		
27/8 50R 14	100		40/17 B16.5	300	
15"			17"		
29/9 50R 15	150		33/12 50R 17	200	
30/9 50R 15	150		35/12 50R 17	200	
33/9 50R 15	200		37/12 50R 17	250	
31/10 50R 15	150		37/13 50R 17	300	
33/10 50R 15	200		40/13 50R 17	300	
31/11 50R 15	120		18"		
32/12 50R 15	200		35/12 50R 18	200	
33/12 50R 15	200		37/12 50R 18	250	
35/12 50R 15	200		20"		
36/12 50R 15	250		35/12 50R 20	200	
37/12 50R 15	250		37/12 50R 20	230	
35/13 50R 15	250				
31/15 50R 15	200				
33/14 50R 15	250				
36/14 50R 15	300				
38/15 50R 15	300				
33/16 50R 15	250				
36/16 50R 15	300				
40/17 B15	300				
44/18 50B 15	350				
16"					
32/9 50R 16	200				
35/10 50R 16	200				
31/12 50R 16	200				
32/12 50R 16	200				
33/12 50R 16	200				
34/12 50R 16	200				
35/12 50R 16	200				
36/12 50R16	250				
37/12 50R 16	250				
33/14 50R 16	300				
38/15 50R 16	300				
16.5"					
31/10 50R 16.5	125				
33/12 50R 16.5	200				
35/12 50R 16.5	200				
37/12 50R 16.5	250				
33/14 50R 16.5	250				
35/14 50R 16.5	250				
38/15 50R 16.5	300				
33/16 50R 16.5	250				
36/16 50R 16.5	300				